
TVAC10100

3.5" TFT Test Monitor

The new ABUS Security-Center test monitor is the ideal tool for all video projects. The monitor is easy to transport and thus delivers the desired performance data wherever needed – video image, voltage, line connectivity. A special highlight is that you can immediately check the images on the monitor while you are adjusting the PTZ camera. This makes adjustments for different positions a lot easier.



Product highlights:

- Measurement of AC/DC voltage and video signal
 - Transition measurement
 - PT-/PTZ camera control (PELCO D/P)
 - Graphical On-Screen-Display (OSD)
 - Battery operation
-

TVAC10100

3.5" TFT Test Monitor

Technical Data

Type of monitor	Test monitor
Screen diagonal	3,5"
Resolution	320 x 240
Image format	4:3
Video system	PAL / NTSC
Signal detection	Automatic
Contrast ratio	350:1
Brightness	300 cd/m2
Color levels	16.7 million
Viewing angle horiz. / vert.	120 (H) x 100 (v)
Response time	25 ms
Frequency range	60 Hz (PAL) / 50 Hz (NTSC)
Functions	AC / DC voltage measurement, cable continuity test, speed dome test, video level measurement, audio test
OSD menu	Graphic On-Screen-Display
OSD languages	German, English, French, Dutch, Danish, Spanish, Italian
Inputs	BNC, Audio, RS-485, cable 1, cable 2
Outputs	BNC
Loudspeaker	1W
Housing material	Plastic
Display surface	Matt
Power supply	9V
Power consumption	400 mA during battery operation
Operating temperature	0° – 45
Dimensions (WxHxD)	156 x 90 x 38 mm
Weight	290 g